

Material review report

MATERIAL REVIEW LOCAL PILOT · PUBLIC NIGERIAN DOCUMENT EVALUATION

Material item	IOM Lagos BOQ · floor Option 1 · public test
Intended use	Public-document evaluation: Option 1 floor tiles, three explicitly selected attributes; not a live project approval
Supplier	CDK Industries · public catalogue evaluation
Selected product	Menandro 600x1200mm Ultra Polish · Menandro
Requirements / submission	Baseline v1 / Revision 1
Recorded by	Public document test reviewer · reviewer@material-review.local
Recorded at	10 October 2026, 15:27 WAT

Revise And Resubmit

Public-document evaluation only. Reviewer selected floor Option 1 (size, polished finish, 8 mm thickness) from the IOM BOQ. The CDK catalogue excerpt has a documented conflict and no thickness statement. This is a test decision, not an IOM approval or rejection of CDK products.

Findings and sources

MISSING EVIDENCE

Thickness

Required: 8 mm

Submitted: Not provided

No supporting statement was found in the fully processed submission scope.

Requirement · Page 9

"OPTION 1: 600x 600 x 8mm thick polish ceramic floor tiles of approved colour laid on screeded bed with cement and sand mortar (1:3) (measured separately)"

Document b95ed3eb-a543-4f99-9f48-a6e9ca82269f · Source block c9531b4a-60df-4e75-ac91-ed536e7682d3

MATCHES

Surface finish

Required: Polished

Submitted: Ultra Polish

The documented value supports the approved requirement.

Requirement · Page 9

"OPTION 1: 600x 600 x 8mm thick polish ceramic floor tiles of approved colour laid on screeded bed with cement and sand mortar (1:3) (measured separately)"

Document b95ed3eb-a543-4f99-9f48-a6e9ca82269f · Source block c9531b4a-60df-4e75-ac91-ed536e7682d3

Supplier · Page 1

"Ultra Polish"

Document 302eb6c8-c63c-4a8c-98e0-f2751643a75d · Source block cea85f8f-d1f5-4f50-bf6d-695facdd8965

CONFLICTS

Dimensions

Required: 600 × 600 mm

Submitted: 600x1200mm

The documented value differs from the approved requirement.

Requirement · Page 9

"OPTION 1: 600x 600 x 8mm thick polish ceramic floor tiles of approved colour laid on screeded bed with cement and sand mortar (1:3) (measured separately)"

Document b95ed3eb-a543-4f99-9f48-a6e9ca82269f · Source block c9531b4a-60df-4e75-ac91-ed536e7682d3

Supplier · Page 1

"600x1200mm"

Document 302eb6c8-c63c-4a8c-98e0-f2751643a75d · Source block cea85f8f-d1f5-4f50-bf6d-695facdd8965

Review record

This report preserves the inputs, machine findings and reviewer corrections at the time of the recorded decision. It describes document evidence; it does not authenticate certificates or verify physical material quality.

Analysis 0ac45ebb-870a-4e9a-b7df-bb2bf1660387

Baseline 28d13056-edd7-4dd2-9eea-78a54694516b · Submission c24364fc-18d6-49c9-a492-d52893516c9a

Model gemini-3.8-flash · Prompt tiles-extraction-1.0 · Rules tiles-1.1.0 · Parser document-parser-1.0